


Product data sheet

Specifications



New Unica - cover frame - 2 gangs - 2 x 2 modules - aluminium

NU400430

Main

Range	New Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Pro
Number of gangs	2 gangs
Installation direction	Horizontal/vertical
Type of frame	Double
Number of modules	2 x 2 modules
Fixing mode	Clip-in
Colour tint	Aluminium

Complementary

Material	Thermoplastic ABS-UV stabilised: cover frame Polycarbonate: intermediate plate
Standards	IEC 60669-1 IEC 60884-1
Width	156 mm
Height	85 mm
Depth	10 mm
Net weight	0.029 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

IK degree of protection	IK04
IP degree of protection	IP21D

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	32.0 g
Package 1 Height	1 cm
Package 1 width	15.7 cm
Package 1 Length	8 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	216.0 g
Package 2 Height	6.4 cm
Package 2 width	12.4 cm
Package 2 Length	18.5 cm
Unit Type of Package 3	P06
Number of Units in Package 3	640
Package 3 Weight	39.876 kg
Package 3 Height	77 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
-------------------	--