


Product data sheet

Specifications

New Unica - cover frame - 3 gangs - 3 x 2 modules - aluminium



NU400630

Main

Range	New Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Pro
Number of gangs	3 gangs
Installation direction	Horizontal/vertical
Type of frame	Triple
Number of modules	3 x 2 modules
Fixing mode	Clip-in
Colour tint	Aluminium

Complementary

Material	Thermoplastic ABS-UV stabilised: cover frame Polycarbonate: intermediate plate
Standards	IEC 60669-1 IEC 60884-1
Width	227 mm
Height	85 mm
Depth	10 mm
Net weight	0.04 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

IK degree of protection	IK04
IP degree of protection	IP21D

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	43.0 g
Package 1 Height	1 cm
Package 1 width	8.5 cm
Package 1 Length	22.7 cm
Unit Type of Package 2	S01
Number of Units in Package 2	10
Package 2 Weight	754.0 g
Package 2 Height	15 cm
Package 2 width	15 cm
Package 2 Length	40 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	272.0 g
Package 3 Height	5.5 cm
Package 3 width	11 cm
Package 3 Length	24.8 cm

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
-------------------	--