

Main

Range	New Unica
Product or component type	Workstation
Number of modules	2 x 10 modules
Fixing mode	Screws
Colour tint	Aluminium

Complementary

Provided equipment	Fixing frame Cover frame
Device mounting	Surface
Cable entry	5 removable plates 2 bottom cable entries 20 mm for diameter 2 bottom cable entries 25 mm for diameter 2 bottom cable entries 45 mm for diameter
Material	ABS (acrylonitrile butadiene-styrene): box ABS (acrylonitrile butadiene-styrene): separator ABS (acrylonitrile butadiene-styrene): cover frame PC: tower
Surface treatment	Antibacterial
Depth	60 mm
Width	300 mm
Height	165 mm
Net weight	0.701 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water

Environment

IK degree of protection IK04

Resistant to crystal cleaner

Resistant to hexane

Resistant to hydrogen peroxide 10 volumes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	870.0 g
Package 1 Height	8 cm
Package 1 width	18 cm
Package 1 Length	31.5 cm
Unit Type of Package 2	S04
Number of Units in Package 2	10
Package 2 Weight	9.572 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Unit Type of Package 3	P06
Number of Units in Package 3	40
Package 3 Weight	45.5 kg
Package 3 Height	75 cm
Package 3 width	60 cm
Package 3 Length	80 cm
-	

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope