


# Product data sheet

Specifications



## New Unica - workstation - flush - 2 x 10 modules - antibacterial - anthracite

NU171054

### Main

Range	New Unica
Product or component type	Workstation
Number of modules	2 x 10 modules
Fixing mode	Claws Embedment
Colour tint	Anthracite

### Complementary

Provided equipment	Cover frame Fixing frame
Device mounting	Flush
Cable entry	4 bottom cable entries 50 x 35 mm for size 25 mm for diameter 8 knock-outs 20 mm for diameter 8 knock-outs 25 mm for diameter 4 bottom cable entries 50 x 35 mm for size 20 mm for diameter
Fire resistance	850 °C, extinction time <30 s
Material	ABS (acrylonitrile butadiene-styrene): separator PC: box ABS (acrylonitrile butadiene-styrene): cover frame PC: tower
Surface treatment	Antibacterial
Depth	62 mm
Width	300 mm
Height	165 mm
Net weight	0.594 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

### Environment

IK degree of protection	IK04
-------------------------	------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	792.0 g
Package 1 Height	8 cm
Package 1 width	18 cm
Package 1 Length	31.5 cm
Unit Type of Package 2	S04
Number of Units in Package 2	10
Package 2 Weight	8.62 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Unit Type of Package 3	P06
Number of Units in Package 3	40
Package 3 Weight	42.12 kg
Package 3 Height	75 cm
Package 3 width	60 cm
Package 3 Length	80 cm

## Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
-------------------	--