
















Table of admissible loads for ..4411

		R		L
				^(*)  + 
				
240 V	Max.	400 W	400 W	400 VA
	Min.	3 W	3 W	3 VA
100 V	Max.	200 W	200 W	200 VA
	Min.	3 W	3 W	3 VA








Do not mix different load types on the same product

(*) Use only with transformers designed to function with electronic switches.

		C/L			
				Dimmable 	Dimmable LED 
					
240 V	Max.	400 VA	200 VA	75 VA or 10 lamps max.	75 VA or 10 lamps max.
	Min.	3 VA	3 VA	3 VA	3 VA
100 V	Max.	200 VA	100 VA	37 VA or 10 lamps max.	37 VA or 10 lamps max.
	Min.	3 VA	3 VA	3 VA	3 VA

Do not mix different load types on the same product

Table of admissible loads for ..4402

		R		L
				^(*)  + 
				
230 V	Max.	400 W	400 W	400 VA
	Min.	40 W	40 W	40 VA
110 V	Max.	200 W	200 W	200 VA
	Min.	20 W	20 W	20 VA

Do not mix different load types on the same product

(*) Use only with transformers designed to function with electronic switches.

- Climatic characteristics

Storage temperature: - 10° C to + 70° C

Use temperature: - 5° C to + 35° C

Cleaning

Clean the surface with a cloth.

Do not use acetone, tar-removing cleaning agents or trichloroethylene.

Caution: Always test before using special cleaning products.

Standards and approvals

Compliance with standards IEC/EN 60669-2-1.

Refer to e.catalogue.