

# Power Supplies Data Sheet

## Single Output Power Supplies

### Power With Confidence

**Current: Up to 30 Amps**

**Voltage: Up to 60 Volts**

**Power: Up to 360 Watts**

#### Switching D.C. Power Supply

The T3PS1XXXX Series is single output, 360 W, switching DC power supply. OVP protects the T3PS1XXXX Series and their load from unexpected conditions. High regulation is maintained at 0.01 %. Remote sensing adds an extra level of precision by compensating for cable losses between the power supply and load. Turning the output On/Off from an external device is available through Remote control terminals. The T3PS1XXXX Series is an ideal solution for power-efficient bench-top or portable applications requiring high regulation.



#### Tools for Improved Debugging

- Dual Measurement Display. ✓ Clearly see your power settings.
- Switched Mode high efficiency Power Supply Design. ✓ Small footprint whilst maintaining high power density.
- Constant Voltage and Constant Current Operation. ✓ Wider application coverage for a more complete solution.
- Rear mounted remote sense terminals. ✓ Ensure that the full voltage gets to your DUT. Sense compensates for wiring losses.
- Remote Output On / Off Control (not programmable) ✓ Turn the output On or Off from an external device.
- Only 128 mm Wide x 151 mm High x 295 mm Deep. Weight Approx. 3.2 kg. ✓ High power / high performance whilst take up the minimum of bench space.

#### Models and Characteristics

T3PS11230	0 – 12 V	0 – 30 A	360 W
T3PS12415	0 – 24 V	0 – 15 A	360 W
T3PS16006	0 – 60 V	0 – 6 A	360 W

# FEATURES AND SPECIFICATIONS



Rear Panel

## T3PS1XXXX Series

- Dual Measurement Display
- 0.01% High Regulation
- Constant Voltage and Constant Current Operation
- High Efficiency
- High Power Density
- Over Voltage Protection
- Remote Output ON/OFF Control

Model	T3PS11230	T3PS12415	T3PS16006
-------	-----------	-----------	-----------

### Output

Voltage	0 ~ 12 V	0 ~ 24 V	0 ~ 60 V
Current	0 ~ 30 A	0 ~ 15 A	0 ~ 6 A

### Constant Voltage Operation

Regulation	Line regulation $\leq 5$ mV, Load regulation $\leq 5$ mV
Ripple & Noise	$\leq 5$ mVrms, 100 mVp-p 20 Hz ~ 20 MHz
RecoveryTime	$\leq 500$ S (50 % Load change, Minimum load 0.5 A)
Temp. Coefficient	$\leq 100$ ppm / °C
Output Range	0 to rating voltage continuously adjustable

### Constant Current Operation

Regulation	Line regulation $\leq 3$ mA, Load regulation $\leq 3$ mA
Ripple Current	$\leq 3$ mArms (T3PS16006) $\leq 10$ mArms (T3PS12415) $\leq 30$ mArms (T3PS11230)
Output Range	0 to rated current continuously adjustable (HI/LO range switchable)

### Meter

Type	3 1/2 digit, 0.39" LED display
Accuracy	$\pm (0.5\% \text{ of rdg} + 2 \text{ digits})$

### Insulation

Chassis and Terminal	20 M $\Omega$ or above (DC 500V)
Chassis and AC Cord	30 M $\Omega$ or above (DC 500V)

### Power Source

	AC 115 V/ 230 V $\pm 15\%$ , 50/60 Hz
--	---------------------------------------

### Dimensions & Weight

	128 (W) x 151 (H) x 295 (D) mm, Approx. 3.2 kg
--	--

## Ordering information

Models	<b>T3PS11230</b>	360 W Switching D.C. Power Supply
	<b>T3PS12415</b>	360 W Switching D.C. Power Supply
	<b>T3PS16006</b>	360 W Switching D.C. Power Supply
Accessories	User manual x 1, Power cord x 3, Test lead GTL-203 A x 1	

Warranty: 3 Years return to Teledyne LeCroy.

# ABOUT TELEDYNE TEST TOOLS



## Company Profile

Teledyne LeCroy is a leading provider of oscilloscopes, protocol analyzers and related test and measurement solutions that enable companies across a wide range of industries to design and test electronic devices of all types. Since our founding in 1964, we have focused on creating products that improve productivity by helping engineers resolve design issues faster and more effectively. Oscilloscopes are tools used by designers and engineers to measure and analyze complex electronic signals in order to develop high-performance systems and to validate electronic designs in order to improve time to market.

The Teledyne Test Tools brand extends the Teledyne LeCroy product portfolio with a comprehensive range of test equipment solutions. This new range of products delivers a broad range of quality test solutions that enable engineers to rapidly validate product and design and reduce time-to-market. Designers, engineers and educators rely on Teledyne Test Tools solutions to meet their most challenging needs for testing, education and electronics validation.

## Location and Facilities

Headquartered in Chestnut Ridge, New York, Teledyne Test Tools and Teledyne LeCroy has sales, service and development subsidiaries in the US and throughout Europe and Asia. Teledyne Test Tools and Teledyne LeCroy products are employed across a wide variety of industries, including semiconductor, computer, consumer electronics, education, military/aerospace, automotive/industrial, and telecommunications.

Distributed by:

## Teledyne LeCroy (US Headquarters)

700 Chestnut Ridge Road  
Chestnut Ridge, NY. USA 10977-6499

Phone: 800-553-2769 or 845-425-2000  
Fax Sales: 845-578-5985  
Phone Support: 1-800-553-2769  
Email Sales: [contact.corp@teledynelecroy.com](mailto:contact.corp@teledynelecroy.com)  
Email Support: [support@teledynelecroy.com](mailto:support@teledynelecroy.com)  
Web Site: <http://teledynelecroy.com/>

World wide support contacts can be found at:  
<https://teledynelecroy.com/support/contact>

World wide instrument service can be found at:  
<https://teledynelecroy.com/support/service.aspx>

RoHS and WEEE information can be found at:  
<https://teledynelecroy.com/support/rohs.aspx>

## Teledyne LeCroy (European Headquarters)

**Teledyne LeCroy GmbH**  
Im Breitenspiel 11c  
D-69126 Heidelberg, Germany

Phone: +49 6221 82700  
Fax: +49 6221 834655  
Phone Service: +49 6221 8270 85  
Phone Support: +49 6221 8270 28  
Email Sales: [contact.gmbh@teledynelecroy.com](mailto:contact.gmbh@teledynelecroy.com)  
Email Service: [service.gmbh@teledynelecroy.com](mailto:service.gmbh@teledynelecroy.com)  
Email Support: [tlc.t3.appsupport.eu@teledyne.com](mailto:tlc.t3.appsupport.eu@teledyne.com)  
Web Site: <http://teledynelecroy.com/>

[teledynelecroy.com](http://teledynelecroy.com)



© 2019 Teledyne Test Tools is a brand and trademark of Teledyne LeCroy Inc. All rights reserved. Specifications, prices, availability and delivery subject to change without notice. Product brand or brand names are trademarks or requested trademarks of their respective holders.

T3 stands for Teledyne Test Tools.

18june19