

mutlipolar terminal plate

**TYP210**  
**TYP310**  
**TYP412**  
**TYP512**  
**TYP612**



item number	max. number of conductors	max. diameter of conductors (mm <sup>2</sup> )	max. load-current capacity (A)	max. voltages (V)	dimension (mm)	weight g / 1 pc	package	konfigurace	color
<b>TYP210</b>	12	2,5	24	400	13,5 x 16 x 95	23	100 pcs in a carton	FA	black
								HA	w hite
<b>TYP310</b>	12	4	32	400	17 x 18 x 106	32	100 pcs in a carton	FA	black
								HA	w hite
<b>TYP412</b>	12	6	41	400	17,5 x 19 x 118	40	100 pcs in a carton	FA	black
								HA	w hite
<b>TYP512</b>	12	10	57	400	21 x 21 x 142	67	100 pcs in a carton	FA	black
								HA	w hite
<b>TYP612</b>	12	16	76	400	22 x 22 x 153	94	50 pcs in a carton	FA	black
								HA	w hite

material: PA6 (halogen-free)

color: black / white

self-snuffing: yes, within 30 s

temperature resistance: -25 - +85 °C

flaming loop test: 850 °C

certification: EN 60998-2-1

storage: ČSN 64 0090