



product description: intended for installation to the distribution of low voltage
 elegant shape
 designed for wall mounting
 possibility to install in places with risk of flammable gases and vapor – danger zone 2
 possibility to install in places with explosive risk of dust – danger zone 22
 not to be mounted on the floor or to be loaded by being stepped on, etc.

material: PVC - Pb-free
 self-snuffing: yes, within 30 s
 temperature resistance: -5 - +60 °C
 flaming loop test: 850 °C
 impact strength: 0,5 J
 protection types: IP30
 fire class for underlying material: A1-F
 inside area: 380+340+380 mm²
 distance base perforation: 200 ±20 mm
 length tolerance: ±10 mm
 weight: 0,59 kg/m
 certification: EN 50085-1 ed.2:06, EN 50085-2-1:07
 storage: ČSN 64 0090



usage of inner trunking cross-section (60%):	orientation cable diameter (mm)	6	7	8	8,5	9	9,5	10	11	12	13	14	15	16
	number of inserted cables		23	15	12	9	9	6	6	6	3	3	3	3

chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate
 NO: aceton, benzen, chlorinated hydrocarbons, tetrachlorocarbon

accessories: instrument carrier PNE 100X20_HB

item number	length	color	package	package - description	note
LE 100_HD	2 m	white RAL 9003	16 m	carton	-
8781_HB		white RAL 9003	2 / 10 / 304 pcs	foil / foil / carton	end
8782_HB		white RAL 9003	2 / 10 / 272 pcs	foil / foil / carton	connecting
8783_HB		white RAL 9003	2 / 90 pcs	foil / carton	bending
8784_HB		white RAL 9003	2 / 68 pcs	foil / carton	branching
8785_HB		white RAL 9003	2 / 10 / 118 pcs	foil / foil / carton	inner corner
8786_HB		white RAL 9003	2 / 10 / 120 pcs	foil / foil / carton	outer corner
RLE 100_HB		white RAL 9003	2 / 410 pcs	foil / carton	spacer