



Tornado T2

Tornado T2 15W CDL E27 220-240V 1PF/6

Tornado has outstanding brightness which makes your colors appear more Vivid. It fits everywhere due to its compact design With comprehensive product range, it allows easy replacement of incandescent lamps all the way

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Product data

| General information | | | |
|------------------------------------|---------------------|--|--|
| Cap-Base | E27 [E27] | | |
| Nominal Lifetime (Nom) | 10000 h | | |
| Switching Cycle | 10000X | | |
| Rated Lifetime (Hours) | 10000 h | | |
| Rated Lifetime (Years) | 10 a | | |
| | | | |
| Light technical | | | |
| Color Code | 865 [CCT of 6500K] | | |
| Luminous Flux (Nom) | 900 lm | | |
| Luminous Flux (Rated) (Nom) | 900 lm | | |
| Color Designation | Cool Daylight | | |
| Lumen Maintenance 2000 h (Nom) | 88 % | | |
| Chromaticity Coordinate X (Nom) | 313 | | |
| Chromaticity Coordinate Y (Nom) | 337 | | |
| Correlated Color Temperature (Nom) | 6500 K | | |
| Luminous Efficacy (rated) (Nom) | 61 lm/W | | |
| | | | |


| Color Rendering Index (Nom) | 80 | | |
|---------------------------------------|-------------|--|--|
| LLMF At End Of Nominal Lifetime (Nom) | 65 % | | |
| | | | |
| Operating and electrical | | | |
| Input Frequency | 50 or 60 Hz | | |
| Power (Nom) | 15.0 W | | |
| Lamp Current (Nom) | 110 mA | | |
| Starting Time (Nom) | 0.3 s | | |
| Warm Up Time to 60% Light (Min) | 5 s | | |
| Warm Up Time to 60% Light (Max) | 40 s | | |
| Power Factor (Nom) | 0.6 | | |
| Voltage (Nom) | 220-240 V | | |
| | | | |
| Controls and dimming | | | |
| Dimmable | No | | |
| | | | |

Tornado T2

| Mechanical and housing | | | |
|-------------------------------|-----------------|--|--|
| Bulb Shape | Spiral | | |
| | | | |
| Approval and application | | | |
| Mercury (Hg) Content (Max) | 2.0 mg | | |
| Mercury (Hg) Content (Nom) | 1.5 mg | | |
| Energy Consumption kWh/1000 h | 15 kWh | | |
| | | | |
| Product data | | | |
| Full product code | 872790092584500 | | |

| Order product name | Tornado T2 15W CDL E27 220-240V 1PF/6 | | |
|---------------------------------|---------------------------------------|--|--|
| EAN/UPC - Product | 8727900925845 | | |
| Order code | 929689114802 | | |
| Numerator - Quantity Per Pack | 1 | | |
| Numerator - Packs per outer box | 6 | | |
| Material Nr. (12NC) | 929689114802 | | |
| Net Weight (Piece) | 0.054 kg | | |
| | | | |

Dimensional drawing



| Product | D (max) | C (max) | F (max) |
|---------------------------------------|---------|----------|---------|
| Tornado T2 15W CDL E27 220-240V 1PF/6 | 51.5 mm | 107.5 mm | 42.5 mm |

Tornado T2 15W CDL E27 220-240V 1PF/6



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2022, August 8 - data subject to change