



Tornado T2

Tornado T2 20W WW E27 220-240V 1PF/6

Tornado has outstanding brightness which makes your colors appear more Vivid. It fits everywhere due to its compact design With comprehensive product range, it allows easy replacement of incandescent lamps all the way

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Product data

General information	
Cap-Base	E27 [E27]
Nominal Lifetime (Nom)	10000 h
Switching Cycle	10000X
Rated Lifetime (Hours)	10000 h
Rated Lifetime (Years)	10 a
Light technical	
Color Code	827 [CCT of 2700K]
Luminous Flux (Nom)	1320 lm
Luminous Flux (Rated) (Nom)	1320 lm
Color Designation	Warm White (WW)
Lumen Maintenance 2000 h (Nom)	88 %
Chromaticity Coordinate X (Nom)	463
Chromaticity Coordinate Y (Nom)	420
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	67 lm/W
	·

82
65 %
50 or 60 Hz
20 W
150 mA
0.3 s
5 s
40 s
0.6
220-240 V
No

Datasheet, 2023, January 18 data subject to change

Tornado T2


Mechanical and housing	
Bulb Shape	Spiral
Approval and application	
Mercury (Hg) Content (Max)	2.0 mg
Mercury (Hg) Content (Nom)	1.5 mg
Energy Consumption kWh/1000 h	20 kWh
Product data	

871016340517900

Order product name	Tornado T2 20W WW E27 220-240V 1PF/6
EAN/UPC - Product	8710163405179
Order code	929689114901
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929689114901
Net Weight (Piece)	0.064 kg

Dimensional drawing

Full product code



Tornado T2 20W WW E27 220-240V 1PF/6

Product	D (max)	C (max)	F (max)
Tornado T2 20W WW E27 220-240V 1PF/6	56.5 mm	116.0 mm	47 mm

