



MASTER MHN-LA

MASTER MHN-LA 2000W/956 400V XWH

Compact guartz metal halide lamps with double-pinch

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

| General information | |
|---------------------------------|---|
| Cap-Base | X528 [X528] |
| Operating Position | P5 [Parallel +/-5D or Horizontal(HOR)] |
| Life to 5% Failures (Nom) | 4500 h |
| Life To 10% Failures (Nom) | 6000 h |
| Life to 20% Failures (Nom) | 8500 h |
| Life to 50% Failures (Nom) | 13000 h |
| | |
| Light technical | |
| Color Code | 956 [CCT of 5600K] |
| Luminous Flux (Rated) (Min) | 170000 lm |
| Luminous Flux (Rated) (Nom) | 190000 lm |
| Color Designation | Daylight |
| Lumen Maintenance 1000 h (Nom) | 94 % |
| Lumen Maintenance 10000 h (Nom) | 63 % |
| Lumen Maintenance 2000 h (Nom) | 89 % |
| Lumen Maintenance 5000 h (Nom) | 76 % |
| Chromaticity Coordinate X (Nom) | 330 |
| Chromaticity Coordinate Y (Nom) | 339 |
| | |

| Correlated Color Temperature (Nom) | 5600 K |
|------------------------------------|--------------|
| Luminous Efficacy (rated) (Nom) | 93 lm/W |
| Color Rendering Index (Nom) | 82 |
| | |
| Operating and electrical | |
| Lamp supply voltage | 400 V [400] |
| Power (Nom) | 2040.0 W |
| Lamp Current Run-Up (Max) | 15 A |
| Lamp Current (EM) (Nom) | 10.3 A |
| Ignition Supply Voltage (Min) | 342 V |
| Voltage (Max) | 235 V |
| Voltage (Min) | 210 V |
| Voltage (Nom) | 225 V |
| | |
| Controls and dimming | |
| Dimmable | No |
| | |
| Mechanical and housing | |
| Bulb Finish | Clear |


Datasheet, 2022, December 17 data subject to change

MASTER MHN-LA

| Cap-Base Information | Cable | |
|--|-----------------|--|
| Bulb Shape | TD40 [TD 40mm] | |
| | | |
| Approval and application | | |
| Mercury (Hg) Content (Nom) | 140 mg | |
| Energy Consumption kWh/1000 h | 2244 kWh | |
| | | |
| UV | | |
| Specific Eff. Radiant Power | 370 mW/klm | |
| | | |
| Luminaire design requirements | | |
| Bulb Temperature (Max) | 920 ℃ | |
| Pinch Temperature (Max) | 350 ℃ | |
| Pinch Temperature (Max)-DUP(do not use) 350 °C | | |
| | | |

| Product data | |
|---------------------------------|----------------------------------|
| Full product code | 871150020073000 |
| Order product name | MASTER MHN-LA 2000W/956 400V XWH |
| EAN/UPC - Product | 8718291548225 |
| Order code | 928072505130 |
| Numerator - Quantity Per Pack | 1 |
| Local code description | LAMP VAP MET MHN-LA 2000W/956 |
| | 400V X528 |
| Numerator - Packs per outer box | 1 |
| Material Nr. (12NC) | 928072505130 |
| Net Weight (Piece) | 0.176 kg |
| ILCOS Code | MN-2000-E-K-/H |
| | |

Dimensional drawing




 Product
 D (max)
 O
 X
 A

 MASTER MHN-LA 2000W/956 400V XWH
 40 mm
 108 mm
 58 mm
 353 mm

MASTER MHN-LA 2000W/956 400V XWH


Photometric data




LDPO_MHN-LA_0004-Spectral power distribution Colour

MASTER MHN-LA

Lifetime





LDLE_MHN-LA_0002-Life expectancy diagram

LDLM_MHN-LA_0002-Lumen maintenance diagram



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.