

Digital Terrestrial HD Receiver **SRT 8211**



Exploring future television with SRT 8211

SRT 8211 origins in the future of terrestrial reception: High Efficiency Video Coding (HEVC) technology, also known as H.265. The receiver offers a vast channel range with optimized image processing of High Definition. Additionally viewers enjoy RSS feeds and weather forecasts. The USB connector allows recording of programmes and playback of multimedia files from external USB devices as well as updates of the receiver software. Your expectations are finally met with STRONG's SRT 8211.

www.strong.tv

- HDTV receiver for DVB-T2 and DVB-T Free-To-Air TV and radio programmes via outdoor or indoor antenna¹
- Supports the new standard HEVC/H.265 and Dolby® Digital Plus²
- New tuner technology for excellent reception
- RSS feeds and weather forecasts via Ethernet
- Display showing channel number in operating mode and time in standby
- 4 favourite lists for TV and radio programmes

REC		EPG		2	4	
USB recording	700 Channels	Programme Guide	Parental Control	RSS feeds	Favourite lists	
D/3	T2 t		rc Adv	/ance	на	DOLBY AUDIO

- Electronic TV Programme Guide (EPG) for on screen programme information of present/following event information up to 14 days³
- Automatic and manual channel scan options
- Teletext, full multi-lingual DVB subtitling and audio track support³
- USB port: recording, multimedia playback⁴, update receiver software via USB storage device
- Excellent audio and video quality



DVB-T2



Digital Terrestrial HD Receiver SRT 8211

- HDTV receiver for DVB-T2 and DVB-T Free-To-Air TV and radio programmes via outdoor or indoor antenna¹
- Supports the new standard HEVC/H.265 and Dolby® Digital Plus²
- New tuner technology for excellent reception
- RSS feeds and weather forecasts via Ethernet
- Display showing channel number in operating mode and time in standby
- 4 favourite lists for TV and radio programmes
- Electronic TV Programme Guide (EPG) for on screen programme information of present/following event information up to 14 days³
- Automatic and manual channel scan options
- Teletext, full multi-lingual DVB subtitling and audio track support³
- USB port: recording, multimedia playback⁴, update receiver software via USB storage device
- Excellent audio and video guality
- Quick and easy installation & user-friendly menu
- USB power control for power saving in standby mode
- 700 channels memory capacity
- Fast channel zapping: sorting by alphabet

- 10 event timers with 4 modes (once, daily, weekly, Monday to Friday)
- High definition on screen display (OSD)
- Booking of events directly from EPG
- Parental lock function for menu and rating control for channel
- Multi-lingual support on screen menu (OSD)
- Many channel handling options: lock, move, delete
- Power on with last viewed channel
- Digital sound through coaxial output (S/PDIF) by connecting to digital amplifier
- User-friendly remote control
- Support of active antenna by 5 V output
- Power saving automatic standby function
- **Connections:** ANT IN, Ethernet, TV SCART, HDMI, S/PDIF coaxial, power switch, USB port
- Accessories: Remote control, 2x AAA batteries
- Depending on local signal conditions Dolby Digital Plus, Dolby Digital and the double-D symbol are registered trademarks of Dolby Laboratories.
- Availability depending on the broadcast
- STRONG cannot guarantee the playback of files although extensions are listed, as it depends on codec, data bit rate and resolution used (all MPEG codec formats are supported).



Tuner:

Input connector: IEC60169-2, female, 75 Ohm nominal Input frequency range: VHF: 174 ~ 230 MHz

UHF:474 ~ 786 MHz DVB-72: -70 dBm ~ -25 dBm Antenna power: 5 V DC, max. 50 mA, short cut protected

Demodulator:

Demodulator: QSPK, 16/64/256 QAM DVB-T (EN 300 744), DVB-T2 (EN 302 755) Transmission mode: normal and extended Guard intervals: DVB-T = 1/32, 1/16, 1/8, 1/4; DVB-T2 = 1/128, 1/32, 1/16, 19/256, 1/8, 19/128, 1/4

Video Decoder: Profile level: MPEG-2 MP@ML, MP@HL, MPEG-4 H.264/AVC, MPEG-4 H.265/ HEVC

Video resolution: 576i, 576p, 720p, 1080i, 1080p Decoding & Video Out: PAL Aspect Ratio: 4:3 and 16:9 Aspect Conversion: Pan & Scan, Letterbox and Combined and Combined

Audio Decoder:

Audio Decoder: Audio support: MPEG-4 Profile Level 4 Dolby Digital Plus*/AC3+/PCM MPEG MusiCam Layer II Sampling rate: 32, 44.1, 48 kHz Audio mode: Stereo, Mono L/R

Connectors: ANT IN - IEC Female

Ethernet S/PDIF (coaxial output) HDMI TV SCART (CVBS, Audio L&R) Power switch USB 2.0 port: 5 V/500 mA (max.) supported

General Data: Power supply: AC 100 – 240 V ~ 50/60 Hz Power consumption: 7 W (typ.), 12 W (max) Power consumption in standby: max 1.0 W Operating temperature: 0 °C ~ +40 °C Storage temperature: -10 °C ~ +50 °C Operating humidity range: 10 ~ 85%, RH, non-condensing Size (WxDxH) in mm: 169 x 102 x 41 Net-weight: 0.36 kg

*Dolby Digital Plus, Dolby Digital and the double-D symbol are registered trademarks of Dolby Laboratories



EAN SRT 8211: 8717185449594

STRONG declares that this item complies with the basic requirements and other relevant regulations of directives CE 2004/108/EC and 73/23/EC, RoHS 2002/95/EC

Subject to alterations. In consequence of continuous research and development technical specifications, design and appearance Subject to alterations. In consequence of continuous research and development: usume any semanation service of products may change HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Lecensing LLC in the United States and other contines, Manufactured under license from Dolby Laboratories. Dolby Audio, alby Digital, Dolby Digital Plus and the double-D symbol are trademarks of Dolby Laboratories. All product names are trademarks or registered trademarks or STRONG 2016. All rights reserved

www.strong.tv