

201.CS2121-5

CHARGING CABLE

T2 20A 1P - T2 20A 1P 3G2,5+1x0,5mm² 5m 3,7 kW



Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|-------------------------------|-----------------------------------|---|
| Product type | CHARGING CABLE | EN 62196-1 (2014) | [European Standard] Plugs, socket-outlets and vehicle couplers. Conductive charging of electric vehicles. Part 1: Charging of electric vehicles up to 250 A a.c. and 400 A d.c. |
| Commercial series | LIBERA Series | | |
| Synthetical description | CHARGING CABLE | EN 62196-2 (2017) | [European Standard] Plugs, socket-outlets and vehicle couplers. Conductive charging of electric vehicles. Part 2: Dimensional interchangeability requirements for a.c. pin and contact-tube accessories |
| Protection degree IP | IP44 | | |
| Rated current | 20A | EN 50620 (2017) | [European Standard] Electric cables - Charging cables for electric vehicles |
| Rated voltage | 230V | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Max power | 3,7kW | | |
| Material | THERMOPLASTIC | | |
| Notes | T2 20A 1P - T2 20A 1P | | |
| EV standard | Type 2 1P+N+E 16A 230V~ 3,7kW | | |
| EV plug | Type 2 1P+N+E 20A 230V~ | | |
| EV connector | Type 2 1P+N+E 20A 230V~ | | |
| Cable section | 3G2,5+1x0,5mm ² | | |
| Cable length | 5m | | |