

## OTL95 ye/gr 1xAl/Cu 6-95mm<sup>2</sup> 1000V Universal terminal

<b>SKU</b>	MAA1095Y10
<b>EAN</b>	4744397013880
<b>Color</b>	Yellow/green
<b>Wire material</b>	Al/Cu
<b>Cross-section min. (mm<sup>2</sup>)</b>	6
<b>Cross-section max. (mm<sup>2</sup>)</b>	95
<b>Input wire min. (mm<sup>2</sup>)</b>	6
<b>Input wire max. (mm<sup>2</sup>)</b>	95
<b>Output wire min. (mm<sup>2</sup>)</b>	6
<b>Output wire max. (mm<sup>2</sup>)</b>	95
<b>Number of connections</b>	2
<b>Nominal current (A)</b>	245 (Cu) / 220 (Al)
<b>Nominal voltage (V)</b>	1000
<b>Service temperature (°C)</b>	80
<b>Material</b>	Tin-plated aluminium, polyamide PA66
<b>Mounting method</b>	DIN rail, screw
<b>Item width (mm)</b>	25
<b>Item length (mm)</b>	84



<b>Item height (mm)</b>	51
<b>Item weight (g)</b>	65
<b>Screw</b>	Hex 6
<b>Tightening torque (Nm)</b>	12 Nm (6 - 25 mm <sup>2</sup> )22 Nm (35 - 95 mm <sup>2</sup> )
<b>IP rating</b>	IP20
<b>Certification</b>	EN 61238-1; EN60947-7-1
<b>Flame resistance</b>	UL94 V0
<b>CN8 code</b>	85369010
<b>Package quantity (pcs)</b>	10

---