



Capsuleline

Capsuleline 50W GY6.35 12V CL 2000h 1CT/10X10F

Low-voltage halogen capsule. Ideal solution for small decorative luminaires. UV-block glass and low-pressure filling allow usage without cover glass. The compact Capsuleline delivers crisp white light over a long lifetime.

Product data


| General Information | |
|---------------------------------------|-----------------------------------|
| Cap-Base | GY6.35 [GY6.35] |
| Philips Code | 14730 |
| Operating Position | UNIVERSAL [Any or Universal (U)] |
| Nominal Lifetime (Nom) | 2000 h |
| Switching Cycle | 8000X |
| Light Technical | |
| Luminous Flux (Nom) | 850 lm |
| Luminous Flux (Rated) (Nom) | 850 lm |
| Correlated Color Temperature (Nom) | 2900 K |
| Luminous Efficacy (rated) (Nom) | 17 lm/W |
| Color Rendering Index (Nom) | 100 |
| LLMF At End Of Nominal Lifetime (Min) | 80 % |
| Operating and Electrical | |
| Power (Rated) (Nom) | 50.0 W |
| Lamp Current (Nom) | 4.17 A |
| Starting Time (Nom) | 0.0 s |
| Warm Up Time To 60% Light (Nom) | instant full light |
| Power Factor (Nom) | 1 |
| Voltage (Nom) | 12 V |

| Controls and Dimming | |
|---------------------------------|--|
| Dimmable | Yes |
| Mechanical and Housing | |
| Bulb Finish | Clear |
| Cap-Base Information | - |
| Approval and Application | |
| Energy Efficiency Label (EEL) | C |
| Energy Consumption kWh/1000 h | 53 kWh |
| Luminaire Design Requirements | |
| Bulb Temperature (Max) | 250 °C |
| Pinch Temperature (Max) | 350 °C |
| Product Data | |
| Full product code | 871150041295950 |
| Order product name | Capsuleline 50W GY6.35 12V CL 2000h 1CT/10X10F |
| EAN/UPC - Product | 8711500412959 |
| Order code | 924892217108 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 100 |
| Material Nr. (12NC) | 924892217108 |

Capsuleline

| | |
|--------------------|-----------------------|
| Net Weight (Piece) | 0.002 kg |
| ILCOS Code | HSG/C/UB-50-12-GY6.35 |

Dimensional drawing



CAP Fighter 14730 50W GY6.35 12V CL

| Product | D (max) | L | C (max) |
|--|---------|-------|---------|
| Capsuleline 50W GY6.35 12V CL 2000h 1CT/10X10F | 12 mm | 30 mm | 44 mm |

