

PRODUCT CARD



PRODUCT CODE: AD-PL-6091WLPMM4

EAN CODE: 5908254822872

CERS LED ceiling lamp with microwave motion sensor, LED 22W, 2000lm, IP65, 4000K, white milky PC, dimming function

The lighting fixture is designed to illuminate areas such as staircases, corridors, verandas, cellars, garages, utility rooms, cloakrooms, outdoor lighting, etc. It is equipped with modern SMD LEDs, which guarantee high energy efficiency and a long life of the plafond, as well as a microwave motion sensor. Depending on the settings, the twilight sensor only switches on the lighting when required. Thanks to four potentiometers, the sensor can be set as required, so that it operates exactly when people are present and moving in the area. In addition, it has a dimming function of up to 20% of its power at a selected time. Adjustable: light duration, light intensity sensitivity, motion detection range and dimming time. Material: polycarbonate (PC) diffuser, unbreakable, milky.



Nominal voltage:
230V



Suitable for lamp power:
22W



Rated luminous flux according to IEC 62722-2-1:
2000lm



Colour temperature:
4000K



Degree of protection (IP):
IP65



Type of sensor:
Microwave

General information

Nominal voltage: 230 V

Lamp type: LED, not replaceable

Suitable for lamp power: 22 W

Rated luminous flux according to IEC 62722-2-1: 2000 lm

With light source: yes

Colour temperature: 4000 K

Max. power: 22W

Beam angle: 360°

Rated life time L70/B50 at 25 °C: 50000 h

Colour rendering index CRI: >80

Standby power: 22 W

Energy efficiency class of the built-in lamp: E

Colour of light: Neutral

Degree of protection (IP): IP65

Impact strength: IK10

Protection class against electric shock: II

Suitable for wall mounting: yes

Suitable for ceiling mounting: yes

Suitable for surface mounting: yes

Material housing: Plastic

Colour housing: White

Material cover: Matt / satin plastic

With movement sensor: yes

With light sensor: yes

Type of sensor: Microwave

Detection range: 4-16 m

Adjustable daylight sensor (LUX): yes

Daylight sensor adjustment range (LUX): <3—2000lux

Adjustable time setting (TIME): yes

Lighting time adjustment range (TIME): min: 10 sek. ± 3 sek.; max: 12 min. ± 1 min.

Adjustment of motion detection range (SENS): yes

Height/depth: 40 mm