

Mountable crosswise on DIN rail. Fire-retardant bridges, IP20 protection class.
Available in three colors.



**A7H,
N7H, PE7H**



**A12H,
N12H, PE12H**



**A15H,
N15H, PE15H**



**A6H-2,
N6H-2, PE6H-2**

Grey		MAD1007A15	MAD1012A15	MAD1015A15	MAD2006A15
Blue		MAD1007N15	MAD1012N15	MAD1015N15	MAD2006N15
Green		MAD1007G15	MAD1012G15	MAD1015G15	MAD2006G15

Technical data

Conductor cross section Cu (mm ²)	1,5 - 16	1,5 - 16	1,5 - 16	8 x 2,5 - 16 4 x 4 - 25
Nominal voltage (V)	690	690	690	500
Nominal current (A)	63	63	63	63
The number of connection points	7	12	15	2 x 6
Tightening torque (Nm)	2	2	2	2
Width / Height / Length (mm)	13 / 27 / 53	13 / 27 / 87	13 / 27 / 106	30 / 27 / 53
Mounting	DIN rail	DIN rail	DIN rail	DIN rail
Weight (g)	28	45	57	88
Package (pcs)	10	10	10	10

Distribution terminals MAG

MAG 25 distribution terminals: Connect copper cables 2.5 to 25 mm². Quick-mounting unit for 35 mm rails. MS 58 contacts, zinc-plated steel screws, IP20 protection. They are tested according to DIN EN 60998.



MAG 25-2 grey



MAG 25-2 blue



MAG 25-2 green

Grey		MAG1250A32	-	-
Blue		-	MAG1250B32	-
Green		-	-	MAG1250G32

Technical data

Conductor cross-section Cu (mm ²)	4 x 2,5 - 25	4 x 2,5 - 25	4 x 2,5 - 25
Nominal voltage AC / DC (V)	1000 / 1500	1000 / 1500	1000 / 1500
Nominal current (A)	80	80	80
Width / Length / Height (mm)	26 / 50,5 / 31,5	26 / 50,5 / 31,5	26 / 50,5 / 31,5
Screw	Pozidriv	Pozidriv	Pozidriv
Tightening torque (Nm)	2,5	2,5	2,5
Mounting	DIN rail	DIN rail	DIN rail
Weight (g)	60	60	60
Package (pcs)	4	4	4