VKS 138B

Application

These are electrodynamic, directional loudspeakers of medium frequency. They are used to be incorporated in three band sound-screen devices.

Description

Frame: material - steel ; covering - zink
Cone: paper
Edge: rubberize cloth
Magnet /oxide/ size: ø86 x ø32 x 10 mm

Technical Data

Passport output :	20 W
Rated impedance :	4 ; 8 ; 15 Ohm
Rated frequency range :	800 - 5000 Hz
Typical sensitivity at 1W per 1m :	88 dB
Weight :	0,8 kg.

Преди използване прочетете внимателно следните указания:
За правилно монтиране и експлоатация:

1. Преди да свържете говорителите към усилвателя, проверете дали захранването е изключено. Изпукването при включване на говорителите може да ги повреди.
2. Когато почиствате говорителите, използвайте мека кърпа и ги забърсвайте внимателно. Не използвайте разредители или препарати.

Монтиране

1. За да монтирате говорителите, първо трябва да определите подходящото място.
2. Наложете модела върху плоскостта и очертайте формата.
3. Изрежете маркираната част.
4. Използвайте окомплектованите винтове и щифтове, за да фиксирате говорителя и плоскостта.
5. Високоговорителят трябва да е закрепен здраво за плоскостта, с цел да се избегнат нежелани вибрации. Закрепването на проводниците към високоговорителите става с кабелна обувка или чрез запояване.