


SKBPC/SBR25A/35A SERIES

FEATURES

- Diffused Junction
- Low Forward Voltage Drop
- High Current Capability
- High Reliability
- High Surge Current Capability
- Ideal for Printed Circuit Boards

MECHANICAL DATA

- Case: Epoxy Case with Heat Sink Internally Mounted in the Bridge Encapsulation
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: As Marked on Body
- Weight: 20 grams (approx.)
- Mounting Position:
Bolt Down on Heatsink With Silicone Thermal Compound Between Bridge and Mounting Surface for Maximum Heat Transfer Efficiency
- Mounting Torque: 20 in lbs. Max.
- Marking: Type Number



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Sing phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%

VOLTAGE RATINGS

Type Number		-00	-01	-02	-04	-06	-08	-10	-12	-14	-16	UNITS
Peak Repetitive Reverse Voltage	VRRM	50	100	200	400	600	800	1000	1200	1400	1600	V
Working Peak Reverse Voltage	VRWM											
DC Blocking Voltage	VR											
Peak Non-Repetitive Reverse Voltage	VRSM	75	150	275	500	725	900	1100	1300	1500	1700	V
RMS Reverse Voltage	VR(RMS)	35	70	140	280	420	560	700	840	980	1120	V

FORWARD CONDUCTION

Type Number		SKBPC/SBR25	SKBPC/SBR35	UNITS
Maximum Average Forward Rectified Current @ Tc = 100°C	IF(AV)	25	35	A
Non-Repetitive Peak Forward Surge Current (No Voltage Reapplid t=8.3ms at 60Hz) (No Voltage Reapplid t=10ms at 50Hz) (100% VRRM Reapplid t=8.3ms at 60Hz) (100% VRRM Reapplid t=10ms at 50Hz)	IFSM	375 360 314 300	500 475 420 400	A
I ² t Rating for fusing (No Voltage Reapplid t=8.3ms at 60Hz) (No Voltage Reapplid t=10ms at 50Hz) (100% VRRM Reapplid t=8.3ms at 60Hz) (100% VRRM Reapplid t=10ms at 50Hz)	I ² t	580 635 410 450	1030 1130 730 800	A ² S
Forward Voltage (per element) @Tj = 25°C, @Ifm=40Apk per single junction	VF	1.26	1.19	V
Peak Reverse Current (per leg) @Tj=25°C At Rated DC Blocking Voltage @Tj=125°C	IR		10 5.0	uA mA
RMS Isolation Voltage from Case to Lead	VISO		2500	V

THERMAL CHARACTERISTICS

Operating Temperature Range	Tj	-40 to + 125	°C
Storage Temperature Range	Tstg	-40 to + 150	°C
Thermal Resistance Junction to Case at DC Operation per Bridge	RθJC	1.42	K/W
Thermal Resistance Case to Heatsink Mounting Surface, Smooth, Flat and Greased	RθCS	0.2	K/W