



Two-component gel

RELICON KH 67

RELICON KH 67 is a transparent, removable, saltwater resistant, flexible two-component gel based on hydrocarbon resins. It is especially suitable for use with junction boxes in low-voltage networks, located in a humid area or in the ground. After curing, RELICON KH 67 is characterised by its excellent resistance to moisture and very good insulating properties as well as good chemical resistance.

Application: Electrical insulation and moisture protection in the low-voltage networks. Particularly suitable for filling of cable junction boxes.

Features and Benefits

- A practical, transparent two-chamber pouch
- Safe-Filling system (SF)
- Excellent flow properties
- Soft elastic, vibration absorbing, removable
- Outstanding insulating properties
- Cures without developing heat
- Saltwater resistant
- Non-toxic, free of silicone and isocyanate
- SVHC-free, contains no hazardous substances, the cured product can be disposed of with house hold waste
- Halogen free



Two-component gel KH 67.

MATERIAL	Gel KH67 (KH67)
Colour	Transparent (CL), Yellow (YE)
Operating Temperature	-40 °C to +90 °C
Mixing Ratio (weight)	100:67
Pot Life	40 min. 23 °C
Density	0.95 g/cm ³ , 20 °C (DIN EN ISO 2811-2)
Dielectric Strength	>15 kV/mm
Viscosity	3000 mPa*s, 5 °C (EN ISO 2555), 2000 mPa*s, 23 °C (EN ISO 2555)
Storage Temperature	+4 °C to +40 °C
Shelf Life	36 months



Silicon free!



TYPE	Pack Cont.	Article-No.
Gel-67-B-SF	180 ml	435-00800
	1,200 ml	435-00804
	250 ml	435-00801
	600 ml	435-00802
	750 ml	435-00803

All dimensions in mm. Subject to technical changes.