

**Product name** : **MoTip Vaseline Spray**  
**Article number** : **090302**

---

## Product description

High quality transparent, universal lubricant and preservative.

## Applications

Battery poles  
Audio controls  
Fasteners (screws, bolts, nuts and nails) Antennas  
Electrical Connections  
Protection for ultra light material (ultra light planes, wind turbines)

## Product characteristics

Water-repellent  
Excellent adhesion  
Prevents wear and sticking  
Can be used in the food industry  
Resistant to weather influences  
Resistant to weak acids and bases  
Excellent corrosion prevention  
Misty spray pattern



## Physical and Chemical Characteristics

Contents	:	500 ml
Basis	:	Vaseline
VOC-content	:	Approximately 85% w/w
Colour	:	White
Scent	:	Characteristic
Relative density at 20°C	:	0,89 g/ml
Yield	:	1,11 g/sec
Vapour pressure at 20°C	:	3 to 4 bar
4 Ball EP-test (ASTM D 2596)	:	3136 N
4 Ball Wear-test (ASTM D 2266)	:	< 0,4 mm
Drop point	:	42°C – 60°C
Temperature resistant	:	-30°C tot +160°C

pH-value : Neutral

## **Usage**

**Before use, carefully read the directions on the packaging and act accordingly.**

The aerosol should have room temperature.

Best processing temperature 5 to 30°C.

Before use, shake the aerosol.

Apply vaseline spray in a thin layer.

Optimum lubrication is obtained after evaporation of the solvent.