

Description:

JDD-MRSG is a newly developed environment-friendly flame retardant heat-shrinkable tube, using modified polymers and cross-linked by electronic accelerator. It offers an economic and efficient solution for the insulation and protection of cable splices and terminals.

Application:

It widely used in the fields of electricity, communication, automotive for connection insulation and rust-proof of metallic product.

Application

It offers an economic and efficient solution for the connection insulation and protection of cable splices and terminals in the electronics, automotive, railway and marine field.

Dimension

| Part No. | Size | | As Supplied (mm) | After Recovery (mm) | | Standard Packin g |
|----------|------|-----|------------------|---------------------|-----------|-------------------|
| | Inch | mm | I.D. | I.D. Max. | W.T. Nom. | m/spool |
| MRSG-0.8 | | 0.8 | 1.1±0.2 | 0.5 | 0.30±0.10 | 200 |
| MRSG-1.0 | 3/64 | 1.0 | 1.5±0.2 | 0.65 | 0.36±0.10 | 200 |
| MRSG-1.5 | 1/16 | 1.5 | 2.0±0.3 | 0.85 | 0.36±0.10 | 200 |
| MRSG-2.0 | 3/32 | 2.0 | 2.5±0.3 | 1.0 | 0.40±0.10 | 200 |
| MRSG-2.5 | | 2.5 | 3.0±0.3 | 1.25 | 0.40±0.10 | 200 |
| MRSG-3.0 | 1/8 | 3.0 | 3.5±0.4 | 1.5 | 0.40±0.10 | 200 |
| MRSG-3.5 | | 3.5 | 4.0±0.4 | 1.75 | 0.44±0.10 | 200 |
| MRSG-4.0 | | 4.0 | 4.5±0.4 | 2.0 | 0.50±0.10 | 200 |
| MRSG-4.5 | 3/16 | 4.5 | 5.0±0.4 | 2.25 | 0.50±0.10 | 200 |
| MRSG-5.0 | | 5.0 | 5.5±0.4 | 2.5 | 0.55±0.10 | 100 |
| MRSG-6.0 | 1/4 | 6.0 | 6.5±0.4 | 3.0 | 0.55±0.10 | 100 |
| MRSG-7.0 | | 7.0 | 7.5±0.5 | 3.5 | 0.55±0.10 | 100 |
| MRSG-8.0 | 5/16 | 8.0 | 8.5±0.5 | 4.0 | 0.60±0.10 | 100 |
| MRSG-9.0 | 3/8 | 9.0 | 9.5±0.5 | 4.5 | 0.60±0.10 | 100 |
| MRSG-10 | | 10 | 10.5±0.5 | 5.0 | 0.60±0.10 | 100 |
| MRSG-11 | | 11 | 11.5±0.5 | 5.5 | 0.60±0.10 | 100 |
| MRSG-12 | | 12 | 12.5±0.5 | 6.0 | 0.60±0.10 | 100 |
| MRSG-13 | 1/2 | 13 | 13.5±0.5 | 6.5 | 0.65±0.10 | 100 |
| MRSG-14 | | 14 | 14.5±0.5 | 7.0 | 0.65±0.10 | 100 |
| MRSG-15 | | 15 | 15.5±0.5 | 7.5 | 0.70±0.10 | 100 |
| MRSG-16 | 5/8 | 16 | 16.5±0.5 | 8.0 | 0.70±0.10 | 100 |
| MRSG-17 | | 17 | 17.5±0.5 | 8.5 | 0.70±0.10 | 100 |
| MRSG-18 | | 18 | 19.0±0.7 | 9.0 | 0.75±0.10 | 100 |
| MRSG-20 | 3/4 | 20 | 21.0±0.7 | 10 | 0.75±0.15 | 100 |
| MRSG-22 | | 22 | 23.0±0.7 | 11 | 0.80±0.15 | 100 |
| MRSG-25 | 1 | 25 | 26.0±0.7 | 12.5 | 0.90±0.15 | 50 |

| | | | | | | |
|----------|-------|-----|----------|------|-----------|----|
| MRSG-28 | | 28 | 29.0±0.5 | 14 | 0.90±0.15 | 50 |
| MRSG-30 | | 30 | 31.5±1.0 | 15 | 0.95±0.15 | 50 |
| MRSG-35 | 1-1/4 | 35 | 36.5±1.0 | 17.5 | 1.0±0.15 | 50 |
| MRSG-40 | 1-1/2 | 40 | 41.5±1.0 | 20 | 1.0±0.15 | 50 |
| MRSG-45 | | 45 | 46.5±1.0 | 22.5 | 1.0±0.15 | 25 |
| MRSG-50 | 2 | 50 | ≥50 | 25 | 1.0±0.15 | 25 |
| MRSG-60 | | 60 | ≥60 | 31 | 1.3±0.15 | 25 |
| MRSG-70 | | 70 | ≥70 | 36 | 1.3±0.15 | 25 |
| MRSG-80 | 3 | 80 | ≥80 | 41 | 1.46±0.20 | 25 |
| MRSG-90 | | 90 | ≥90 | 46 | 1.46±0.20 | 25 |
| MRSG-100 | 4 | 100 | ≥100 | 51 | 1.46±0.20 | 25 |
| MRSG-120 | 5 | 120 | ≥120 | 61 | 1.56±0.20 | 25 |
| MRSG-150 | 6 | 150 | ≥150 | 76 | 1.56±0.20 | 25 |
| MRSG-180 | 7 | 180 | ≥180 | 91 | 1.56±0.20 | 25 |