

DiSEqC Switch | 4 to 1 | F-Connector | 950 - 2400 MHz

General information

This DiSEqC switch enables you to receive four satellites with a single receiver. The switch has a low insertion loss and is well-protected against bad weather conditions.

Features

- Durable and weatherproof housing for long lifespan
- Low insertion loss for a high-quality signal
- 4 inputs and 1 output for the reception of 4 satellites with a single receiver

Specifications

DiSEqC version:	2.0
Satellite frequency range:	950 - 2400 MHz
Power consumption in operating mode:	10 mA
Insertion loss:	3 dB
Input voltage:	12-20 VDC
Number of inputs:	4
Type:	DiSEqC Switch
Number of outputs:	1
Colour:	Silver/White
Material:	Zinc
Connector type:	F-connector
Connection output:	1x F-Connector Female
Connection input:	4x F-Connector Female
Feature:	Rain Protection Cap

Package contents

DiSEqC Switch



Sales information

Order code:	SSWI400WT
Product description:	DiSEqC Switch 4 to 1 F-Connector 950 - 2400 MHz
Packaging:	Giftbox with eurolock
Brand name:	Nedis



5 412810 298310

Quantity	LxWxH (mm)	Weight
1	80x83x22	55 gr.
200	355x250x435	14120 gr.