

Description:

JDD-MRSG is a newly developed environment-friendly flame retardant heat-shrinkable tube, using modified polymers and cross-linked by electronic accelerator. It offers an economic and efficient solution for the insulation and protection of cable splices and terminals.

Application:

It widely used in the fields of electricity, communication, automotive for connection insulation and rust-proof of metallic product.

Application

It offers an economic and efficient solution for the connection insulation and protection of cable splices and terminals in the electronics, automotive, railway and marine field.

Dimension

Part No.	Size		As Supplied (mm)	After Recovery (mm)		Standard Packin g
	Inch	mm	I.D.	I.D. Max.	W.T. Nom.	m/spool
MRSG-0.8		0.8	1.1±0.2	0.5	0.30±0.10	200
MRSG-1.0	3/64	1.0	1.5±0.2	0.65	0.36±0.10	200
MRSG-1.5	1/16	1.5	2.0±0.3	0.85	0.36±0.10	200
MRSG-2.0	3/32	2.0	2.5±0.3	1.0	0.40±0.10	200
MRSG-2.5		2.5	3.0±0.3	1.25	0.40±0.10	200
MRSG-3.0	1/8	3.0	3.5±0.4	1.5	0.40±0.10	200
MRSG-3.5		3.5	4.0±0.4	1.75	0.44±0.10	200
MRSG-4.0		4.0	4.5±0.4	2.0	0.50±0.10	200
MRSG-4.5	3/16	4.5	5.0±0.4	2.25	0.50±0.10	200
MRSG-5.0		5.0	5.5±0.4	2.5	0.55±0.10	100
MRSG-6.0	1/4	6.0	6.5±0.4	3.0	0.55±0.10	100
MRSG-7.0		7.0	7.5±0.5	3.5	0.55±0.10	100
MRSG-8.0	5/16	8.0	8.5±0.5	4.0	0.60±0.10	100
MRSG-9.0	3/8	9.0	9.5±0.5	4.5	0.60±0.10	100
MRSG-10		10	10.5±0.5	5.0	0.60±0.10	100
MRSG-11		11	11.5±0.5	5.5	0.60±0.10	100
MRSG-12		12	12.5±0.5	6.0	0.60±0.10	100
MRSG-13	1/2	13	13.5±0.5	6.5	0.65±0.10	100
MRSG-14		14	14.5±0.5	7.0	0.65±0.10	100
MRSG-15		15	15.5±0.5	7.5	0.70±0.10	100
MRSG-16	5/8	16	16.5±0.5	8.0	0.70±0.10	100
MRSG-17		17	17.5±0.5	8.5	0.70±0.10	100
MRSG-18		18	19.0±0.7	9.0	0.75±0.10	100
MRSG-20	3/4	20	21.0±0.7	10	0.75±0.15	100
MRSG-22		22	23.0±0.7	11	0.80±0.15	100
MRSG-25	1	25	26.0±0.7	12.5	0.90±0.15	50

MRSG-28		28	29.0±0.5	14	0.90±0.15	50
MRSG-30		30	31.5±1.0	15	0.95±0.15	50
MRSG-35	1-1/4	35	36.5±1.0	17.5	1.0±0.15	50
MRSG-40	1-1/2	40	41.5±1.0	20	1.0±0.15	50
MRSG-45		45	46.5±1.0	22.5	1.0±0.15	25
MRSG-50	2	50	≥50	25	1.0±0.15	25
MRSG-60		60	≥60	31	1.3±0.15	25
MRSG-70		70	≥70	36	1.3±0.15	25
MRSG-80	3	80	≥80	41	1.46±0.20	25
MRSG-90		90	≥90	46	1.46±0.20	25
MRSG-100	4	100	≥100	51	1.46±0.20	25
MRSG-120	5	120	≥120	61	1.56±0.20	25
MRSG-150	6	150	≥150	76	1.56±0.20	25
MRSG-180	7	180	≥180	91	1.56±0.20	25