

Lamps with glass wedge bases for cars




Product benefits


- Wide product range
- Reliable quality

Product features


Original spare parts




Product line drawing





Product line drawing




Product line drawing








Product line drawing



Product line drawing



Product line drawing



Product line drawing



Base





IEC 7005-94 DIN 49642 T 2

Base

Technical data

Product description	ECE category	Power input	Nominal wattage	Nominal voltage	Luminous flux	Luminous flux tolerance
921	W16W	19.4 W	16.00 W	12 V	310 lm	±20 %
921NA	WY16W	19.4 W	16.00 W	12 V	190 lm	±20 %
2723	W2,3W	2.3 W	2.30 W	12 V	18.6 lm	±20 %
7515	W21/5W	25 / 6 W		12 V	440/35 lm	±15 / ±20 %
7505	W21W	25 W	21.00 W	12 V	460 lm	±15 %
2821	W3W	3 W	3.00 W	12 V	22 lm	±30 %
2825	W5W	5 W	5.00 W	12 V	50 lm	±20 %
7504 ¹⁾	WY21W	25 W	21.00 W	12 V	280 lm	±20 %
2827 ¹⁾	WY5W	5 W	5.00 W	12 V	30 lm	±20 %
2721	-	1.22 W	1.20 W	12 V	7.5 lm	±20 %
2722	-	2 W	2.00 W	12 V	12 lm	±20 %
2820	-	2.2 W	2.00 W	12 V	13.5 lm	±25 %
	•		·			

Product description	Power input tolerance	Base (standard designation)	Lifespan B3	Lifespan Tc	Length	Diameter
921	±10 %	W2.1x9.5d	175 h	545 h	38.0 mm	16.0 mm
921NA	±10 %	W2.1x9.5d	400 h	1000 h	38.1 mm	16.0 mm
2723	±8 %	W2x4.6d	350 h	1200 h	20.0 mm	5.0 mm
7515	±6 / ±10 %	W3x16q	400 / 600 h ²⁾	3000 / 3000 h ²⁾	47.5 mm	20.0 mm
7505	±6 %	W3x16d	400 h	600 h	47.5 mm	20.0 mm

Product description	Power input tolerance	Base (standard designation)	Lifespan B3	Lifespan Tc	Length	Diameter
2821	±10 %	W2.1x9.5d	1300 h	4000 h	26.8 mm	10.3 mm
2825	±10 %	W2.1x9.5d	350 h	1000 h	26.8 mm	10.0 mm
7504 ¹⁾	±6 %	WX3x16d	400 h	600 h	47.5 mm	20.0 mm
2827 ¹⁾	±10 %	W2.1x9.5d	350 h	1000 h	26.8 mm	10.0 mm
2721	±15 %	W2x4.6d	500 h	2000 h	22.6 mm	5.0 mm
2722	±15 %	W2x4.6d	1300 h	4000 h	20.0 mm	5.0 mm
2820	±10 %	W2.1x9.5d	600 h	4000 h	26.8 mm	10.0 mm

Product description	Test voltage	New article
921	13.5 V	
921NA	13.5 V	NEW
2723	13.5 V	
7515	13.5 V	
7505	13.5 V	
2821	13.5 V	
2825	13.5 V	
7504 ¹⁾	13.5 V	
2827 ¹⁾	13.5 V	
2721	13.5 V	
2722	13.5 V	
2820	13.5 V	

1) Amber lamp for clear indicators

²⁾ Filament 1

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.