

Product name : **MoTip V Belt Spray**

Product description

High quality spray to protect V-Belts and to remedy and prevent slipping.

Applications

Vehicles	Machinery
Conveyer belts	Agricultural Machinery
Drill Presses	Concrete mixers
Lathes	Lawn mowers
Generators	Pumps
Compressors	Forklift trucks
Milling machines	

Product characteristics

User-friendly
Remedies and prevents slipping and creaking
Excellent adhesion
Lasting protection
Dilatant
Resistant to weather influences Conditions V-Belts
Delays the wear of V-Belts
Directed jetspray

Physical and Chemical Characteristics

Contents	:	500 ml
Basis	:	Polyalphaolefine
VOC-content	:	Approximately 93% w/w
Colour	:	Transparent
Scent	:	Characteristic
Relative density at 20°C	:	0,89 g/ml
Yield	:	1,15 g/sec
Vapour pressure at 20°C	:	3 to 4 bar



Usage

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol should have room temperature.
Best processing temperature 5 to 30°C.
Before use, shake the aerosol.

Switch off the engine.

Apply the V-Belt Spray in an equal, thin layer on the threads of the V-Belt and allow to take effect. After evaporation of the solvent, the engine can be switched on.