
Product name	:	MoTip Ceramic Grease
Article number	:	090307
Supplier / Producer	:	MOTIP DUPLI B.V. Wolframweg 2 NL-8471 XC WOLVEGA
		Telephone number +31 561 – 69 44 00
		Telefax number +31 561 – 69 44 31

Product description

High quality metal-free ceramic grease, to treat parts which are liable to heavy workload and/or which are exposed to very high temperatures.

Applications

ABS brake systems
Lambda sensors
Brake parts
Exhaust parts
Screwed connections, which are exposed to high temperature
Industrial ovens

Product characteristics

Protects against electrolytic corrosion
High thermal stability
Resistant to chemicals and weather influences
Resistant to water, salt and weak acids and bases
Excellent adhesion
Prevents wear and sticking
Extremely suitable to mount ABS brake systems and lambda sensors
Directed jetspray
Simplifies the future removal

Physical and Chemical Characteristics

Contents	:	500 ml
Basis	:	Very fine ceramic particles
VOC-content	:	Approximately 68% w/w
Colour	:	White
Scent	:	Characteristic
Appearance	:	Pasty
Relative density at 20°C	:	1,26 g/ml
Yield	:	1,65 g/sec
Vapour pressure at 20°C	:	3 to 4 bar
Temperature resistant	:	-40°C to +1.200°C



Usage

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol should have room temperature.
Best processing temperature 5 to 30°C.
Before use, shake the aerosol.

Apply ceramic grease. The specific lubrication properties of ceramic grease will be obtained after evaporation of the solvent (approximately 1 minute).